



## A-A-208C Marking Ink

### Technical Data Sheet

**Description:** A-A-208C is an opaque marking stencil Ink for use on porous or non-porous surfaces.

**Physical Properties:**

<b>Colors:</b>	All Fed Std. 595B
<b>Finish:</b>	Flat, Gloss, Semi-Gloss

**Application Characteristics:**

- (1) High Opacity
- (2) Use on Porous or Non-Porous Surfaces
- (3) Resistant to Smearing
- (4) Flat, Uniform Finish

**APPLICATION & REDUCTION:** Apply by brush, roller, or spray methods. For brush and roll, thin, if necessary, with Xylene at 10% by volume. For spray application, thin with MIL-T-81772B Ty. III Thinner at approximately 10-15% by volume or as needed for proper atomization based on spray equipment being used. For roller / stamp application, thin Type I material 25-50% as needed to slow dry time. Type IV material is roller ready. If using rollers, a roller compatible with xylenes and acetones and other strong solvents must be chosen otherwise, rollers may be damaged.

**SURFACE PREPARATION:** Surface must be clean, dry and free of all contamination before application of coating. Prime per specification requirements and/or recommendations.

**PRECAUTIONS:**

- Contents are FLAMMABLE.
- Keep away from heat and open flame.
- KEEP OUT OF THE REACH OF CHILDREN.
- Do not take internally.
- Avoid breathing vapor or mist.
- Do not use in tank or pit without proper protection.
- Read Material Safety Data Sheet before use of this product