



Technical Data Sheet

A-A-59166

WALKWAY COMPOUND-NONSLIP Type I & II

- PRODUCT:** A non-slip walkway coating for the exterior of aircraft surfaces.
- DESCRIPTION:** A-A-59166 WALKWAY COATING is a nonslip walkway compound coating for use on walkways of exterior aircraft surfaces. Type I is smooth and can be applied by brushing or rolling, as well as spraying. Type II contains grit for additional non-skid properties and is for brushing and rolling application only.
- PROPERTIES:**
- COLORS:** Per Fed.Std. 595B
 - TYPE I: Smooth Texture
 - TYPE II: Grit Added
 - FINISH:**
 - Lusterless SOLIDS(Weight): 52 - 65%
 - DRYING TIMES:**
 - TACK FREE - 15 Minutes
 - RECOAT - 30 Minutes
 - DRY THROUGH - 6 Hours
 - FULL HARDNESS -24 Hours
 - Full Cure -7 days
- ADVANTAGES:**
1. Non-Slip.
 2. Air Dry.
 3. Brush-able.
 4. Durable.
 5. Fast Dry.
- USES:**
1. Exterior Aircraft Walkways.
 2. Heavy Traffic Areas.
 3. Non-Slip Requirements.

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com



Technical Data Sheet

APPLICATION: Apply by brush or roll methods (or spray for Type I). Thin with MIL-T-81772B Type III Reducer or TT-X-916 Xylene as needed to facilitate proper flow. For Type II, Do not over brush so that an even distribution of the grit is achieved.

SURFACE PREPARTAION: Surface must be completely clean, structurally sound, and free of all contaminants (including dirt, wax, loose paint, grease, etc.). Do not paint over moist / wet surfaces.

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN.
USE WITH ADEQUATE VENTILATION.
AVOID CONTACT WITH SKIN AND EYES.
READ MATERIAL SAFETY DATA SHEET BEFORE USING.
CONTENTS ARE FLAMMABLE.

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com