



Technical Data Sheet

MIL-L-19537

ACRYLIC NITRO-CELLULOSE GLOSS LACQUER

PRODUCT: A general purpose exterior protective coating for metal surfaces. MIL-L19537C is particularly formulated for resistance to lubricating oil, and is primarily intended for spray application. Available in all gloss Fed-STD 595 colors.

PROPERTIES:

COLORS: All Fed-STD 595B

GRIND: Not Under 7.5

NON-VOLATILE: Not Under 40%

VISCOSITY (Reduced) #4 Ford Cup: Not Over 20 Sec.

DRYING TIME AT 75 DEGREES F: Dry hard within 40 Minutes

USES:

- Aerospace Applications
- Machinery
- Steel Surfaces
- Equipment
- Office Equipment
- Computer Cabinets

SURFACE PREPARATION: Surface must be clean, dry and free of all contamination before application of gloss lacquer. Prime per specification requirements.

STEEL: Surface must be clean and free of all oil, grease and foreign material. Badly rusted or pitted steel should be cleaned by commercial sandblasting and primed the same day.

PRECAUTIONS:

Contents are FLAMMABLE.

Keep away from heat and open flame.

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com