



MIL-V-16399A Moisture Resistant Varnish, Air Dry

Technical Data Sheet (Page 1 of 2)

Description:

A moisture and fungus resistant varnish for the treatment of communications, electronic and related equipment. May also be used on tools and materials that are to be transported by ship. Dries to a smooth, hard film that resists cracking and splintering.

Physical Properties:

Color:	Clear
Finish:	Gloss
Total Solids:	51 – 54%
Drying Times:	
Set-To-Touch:	60 Minutes
Tack Free:	5 Hours

Typical Uses:

- (1). Electronic Equipment
- (2). Communications Equipment
- (3). Electrical Equipment
- (4). Tools
- (5). Electric Parts/Wires

Application Characteristics:

- (1). Fast Dry
- (2). Moisture Resistant
- (3). Fungus Resistant
- (4). Air Dry

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com



MIL-V-16399A Moisture Resistant Varnish, Air Dry

Technical Data Sheet (Page 2 of 2)

APPLICATION & REDUCTION: MIL-V-16399A can be applied by brush, roll, or spray. Vigorously shake can for one minute to thoroughly mix coating. Shake can occasionally while spraying. Hold can approximately 12" from surface to be painted.

SURFACE PREPARATION: Surface must be clean, dry, and properly prepared before application.

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN.

USE WITH ADEQUATE VENTILATION.

AVOID CONTACT WITH SKIN AND EYES.

READ MATERIAL SAFETY DATA SHEET BEFORE USING.

KEEP FROM FREEZING

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com