



Technical Data Sheet

TT-F-325A TY. I

PRODUCT DESCRIPTION: Lacquer Stick

APPLICATION INSTRUCTIONS: Remove film from tip before use. Rub lacquer-stik into engraving. Wipe off excess around engraving with a soft cloth. On rough surfaces excess wet paint can be removed by lightly rubbing with a cloth dipped in mineral oil. For dried paint use mineral spirits or alcohol.

DRY TIME: Initial tack-free dry time is about 12 hours. Complete dry time is about 24 hours.

SPECIFICATIONS MET:

- TT-F-325A, TYPE I
- MIL-STD 171, FINISH NO. 30.1.1, TYPE I
- BLACK ONLY: COLOR PER FED-STD-595, HUE ONLY 37030-37038
- CAN BE USED UNDER MIL-STD-130J PER TABLE 1, MARKING METHODS, ENGRAVING, AS LONG AS SECTION 4.3, PERMANENCY AND LEGIBILITY CRITERIA ARE VERIFIED BY CUSTOMER.

NOTE:

FEDERAL STANDARD TT-F-325A CALLS FOR:

WHITE #37778

BLACK # 37038

RED #31136

THESE COLORS ARE REFERENCED IN FEDERAL STANDARD 595B

LA-CO COLORS ARE CLOSEST TO:

WHITE #37925

BLACK #37038

RED #31350

YELLOW #33696

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com