



TT-L-20A Lusterless Lacquer

Technical Data Sheet (Page 1 of 2)

Physical Properties:

Colors:	All Fed Std. 595B
Grind:	Not Under 5
Specular Gloss:	Varies by Color
Viscosity (Reduced) #4 Ford Cup:	Not Over 27 Seconds
Drying Time At 75 Degrees F:	
Dust Free:	3 – 5 Minutes
Dry Hard:	40 Minutes

Typical Uses:

- (1) Ammunition
- (2) Machinery
- (3) Steel Surfaces
- (4) Equipment
- (5) Camouflage Requirements

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com



TT-L-20A Lusterless Lacquer

Technical Data Sheet (Page 2 of 2)

APPLICATION & REDUCTION:

TT-L-20A should only be applied by spray application due to its fast dry properties. Thin TT-L-20A approximately 10-15% by volume with MIL-T-81772B Type 3 Thinner or enough to get proper atomization through your spray equipment. Spray one tack coat followed by one full wet coat. The use of MIL-C- 8514C and TT-P-1757A Primers are normally required for use under this lacquer topcoat. This is also available in aerosolized products. Thinning does not apply to aerosolized products.

SURFACE PREPARATION:

Surface must be clean, dry, and free of all contamination before application of primer.

STEEL:

Surface must be clean and free of all oil, grease, and foreign material. Badly rusted or pitted steel should be cleaned by commercial sandblasting and primed the same day.

PRECAUTIONS:

Contents are FLAMMABLE.

Keep away from heat and open flame.

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally.

Avoid breathing vapor or mist.

Do not use in tank or pit without proper protection.

Read Material Safety Data Sheet before use of this product.

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com