



Technical Data Sheet

**TT-L-26C
LACQUER**

PRODUCT: This specification covers an industrial grade clear and pigmented gloss lacquer for brush application. This product is recommended for interior or exterior use on primer metal or sealed wood surfaces. The clear lacquer can be used directly on copper and brass surfaces without priming. Meets government specification TT-L-26C.

PROPERTIES:

COLORS.....	All Fed-STd 595B
GRIND.....	N/A
SPECULAR GLOSS.....	FULL VISCOSITY
#4 Ford Cup.....	27 TO 40 Sec.

DRYING TIME AT 75 DEGREES F:

DUST FREE: 15 MINUTES MAX.
DRY THROUGH: 2 HRS. MAX.

USES:

1. Machinery
2. Copper or Brass
3. Steel Surfaces
4. Equipment
5. Sealed wood

PRECAUTIONS:

CONTENTS ARE FLAMMABLE.

KEEP AWAY FROM HEAT AND OPEN FLAME.

KEEP OUT OF THE REACH OF CHILDREN.

DO NOT TAKE INTERNALLY

AVOID BREATHING VAPOR OR MIST.

DO NOT USE IN TANK OR PIT WITHOUT PROPER PROTECTION.

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com