



## Technical Data Sheet

### TT-L-50G Acrylic lacquer

**PRODUCT:** An air-dry acrylic lacquer in aerosol cans or bulk.

**DESCRIPTION:** *TT-L-50G Type I Nitrocellulose Lacquer or Type II Acrylic* is a high-grade lacquer coating supplied in pressurized dispensers or bulk for general purpose applications. A full range of colors is available including clear.

**PROPERTIES:**

COLORS: Clear & Full Range  
FINISH: Flat - High Gloss  
SOLIDS (Weight): 40 - 64%  
FINESS OF GRIND: 5 - 7

**DRYING TIMES:**

DUST FREE: 5 Minutes  
DRY HARD: 10 Minutes  
DRY THROUGH: 2 Hours

**ADVANTAGES:**

1. Fast Dry
2. Acrylic Resin
3. Durable
4. Air Dry

**USES:**

1. Metal
2. Wood
3. Paper
4. Tools
5. Garden Implements



## Technical Data Sheet

---

**APPLICATION AND REDUCTION:** Vigorously shake can for one minute to thoroughly mix coating. Shake can occasionally while spraying. Hold aerosol can approximately 12" from surface to be painted. Non-aerosol bulk form can be applied by conventional or airless spray application. For spraying, thin up to 10% or as needed with

MIL-T-81772B TY.3 Thinner. For brushing, reduce up to 10% with MIL-T-81772B TY.3 Thinner. Brush small areas only.

### **PRECAUTIONS:**

KEEP OUT OF REACH OF CHILDREN.  
USE WITH ADEQUATE VENTILATION.  
AVOID CONTACT WITH SKIN AND EYES.  
READ MATERIAL SAFETY DATA SHEET BEFORE USING.  
KEEP FROM FREEZING, CONTAINS WATER.