



## Technical Data Sheet

**TT-V-109C**  
**SPAR VARNISH**

**PRODUCT:** An air dry, moisture resistant clear gloss phenolic-alkyd varnish.

**DESCRIPTION:** This coating is a moisture resistant phenolic-alkyd varnish

**PROPERTIES:** COLOR - Clear  
FINISH - Gloss  
SOLIDS(Weight) - 57 - 60%

**DRYING TIMES:** SET-TO-TOUCH - Within 60 Minutes  
DRY TACK FREE - Within 5 Hours

**ADVANTAGES:**

1. Fast Dry
2. Moisture Resistant
3. Air Dry

**USES:**

1. Electronic Equipment
2. Communications Equipment
3. Electrical Equipment
4. Tools
5. Electric Parts/Wires

**APPLICATION:** Surface must be clean, dry and properly prepared before application. May be applied by brush, roll or spray.

*AEROSOL CANS:* Vigorously shake can for one minute to thoroughly mix coating. Shake can occasionally while spraying. Hold can approximately 12" from surface to be painted.

***Fast. Reliable. Accurate. Superior Coatings of America***

Address: P.O. Box 409 Clinton, MI 49236    Office Phone: 734-580-2089    Email: sales@superiorsalesdist.com  
[www.superiorsalesdist.com](http://www.superiorsalesdist.com)



## Technical Data Sheet

---

**PRECAUTIONS:**

KEEP OUT OF REACH OF CHILDREN.

USE WITH ADEQUATE VENTILATION.

AVOID CONTACT WITH SKIN AND EYES.

READ MATERIAL SAFETY DATA SHEET BEFORE USING.

CONTENTS ARE FLAMMABLE.

***Fast. Reliable. Accurate. Superior Coatings of America***

Address: P.O. Box 409 Clinton, MI 49236    Office Phone: 734-580-2089    Email: [sales@superiorsalesdist.com](mailto:sales@superiorsalesdist.com)  
[www.superiorsalesdist.com](http://www.superiorsalesdist.com)