



TT-V-109C Spar Varnish, Air-Dry Technical Data Sheet

Description: This coating is a moisture resistant phenolic-alkyd varnish

Physical Properties:

Color:	Clear
Finish:	Gloss
Solids (Weight):	57 – 60%
Drying Times:	
Set-To-Touch:	Within 60 Minutes
Tack Free:	Within 5 Hours

Application Characteristics:

- (1) Fast Dry
- (2) Moisture Resistant
- (3) Air Dry

Typical Uses:

- (1) Electronic Equipment
- (2) Communications Equipment
- (3) Electrical Equipment
- (4) Tools
- (5) Electric Parts/Wires

APPLICATION & REDUCTION: Surface must be clean, dry, and properly prepared before application. May be applied by brush, roll or spray.

AEROSOL CANS: Vigorously shake can for one minute to thoroughly mix coating. Shake can occasionally while spraying. Hold can approximately 12" from surface to be painted.

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN.
USE WITH ADEQUATE VENTILATION.
AVOID CONTACT WITH SKIN AND EYES.
READ MATERIAL SAFETY DATA SHEET BEFORE USING.
CONTENTS ARE FLAMMABLE.

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com