



Technical Data Sheet

TT-V-119D
SPAR VARNISH

PRODUCT: An air dry, moisture resistant clear gloss phenolic varnish.

DESCRIPTION: This coating is a moisture resistant phenolic varnish

PROPERTIES: COLOR - Clear
FINISH - Gloss
SOLIDS(Weight) - 57 - 60%

DRYING TIMES: SET-TO-TOUCH - Within 60 Minutes
DRY TACK FREE - Within 5 Hours

ADVANTAGES:

1. Fast Dry
2. Moisture Resistant
3. Air Dry

USES:

1. Electronic Equipment
2. Communications Equipment
3. Electrical Equipment
4. Tools
5. Electric Parts/Wires

APPLICATION: Surface must be clean, dry and properly prepared before application. May be applied by brush, roll or spray.

AEROSOL CANS: Vigorously shake can for one minute to thoroughly mix coating. Shake can occasionally while spraying. Hold can approximately 12" from surface to be painted.

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com



Technical Data Sheet

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN.

USE WITH ADEQUATE VENTILATION.

AVOID CONTACT WITH SKIN AND EYES.

READ MATERIAL SAFETY DATA SHEET BEFORE USING.

CONTENTS ARE FLAMMABLE.

Fast. Reliable. Accurate. Superior Coatings of America

Address: P.O. Box 409 Clinton, MI 49236 Office Phone: 734-580-2089 Email: sales@superiorsalesdist.com
www.superiorsalesdist.com